

## OI-9100 WireFree Signal Strength Meter

The WireFree Gen II View OI-9100 is a hand held signal strength meter specifically engineered to show the status of any WireFree Gen II gas detection device within range.

The View features a 4-line scrollable display. Using a 4-column read, the View is capable of revealing the Channel, Reading, Signal Strength, and Time Since Last Message of any WireFree device on site, as well as the Sensor, Gas, and Battery. The View contains a 900 MHz 200 mW or 2.4 GHz ISM, 100 mW radio, ensuring prompt and accurate communication with other WireFree devices.

The ability of the View to continuously notify the user of each WireFree device's status at a particular site make the device a truly phenomenal safety product to be introduced into the industry.



### Specifications

## Specifications

- Operating Power: Two 3.7V Lithium Ion rechargeable batteries
- Battery Life: 16 hours (continuous use); time will vary with battery life
- Enclosure: Black aluminum; powder-coated
- Enclosure Dimen.: 4.875" x 4" x 1.188"
- Radio: 2.4 GHz ISM, 100 mW  
900 MHz, 200 mW
- Fuses: PTC (automatic resettable); Non end-user replaceable
- Display: 4 x 20 character alpha/numeric LCD
- Warranty: Hardware: One-year (limited)

Dimensions

