



ULTRAVIOLET-INFRARED FLAME DETECTOR

OmniGuard® model 860

The OmniGuard® model 860 UV/IR flame detector is designed to detect unwanted fires, and output appropriate alarm information. The model 860 senses ultraviolet radiation and infrared radiation in the appropriate wavelengths for very early fire detection. And, using the patented Fire Event Analysis algorithm, is also able to distinguish between real fire and non-fire events providing superior false alarm immunity. The technology has proven itself over decades of reliable service.

The model 860 is available in two versions, one for hydrocarbon fires only, and one for hydrocarbon and certain non-hydrocarbon fires. This dual capability provides the unique capability of providing fire detection for a broad range of fuels with a single unit. Both versions are available with an automatic self-test function to monitor the detector's ability to sense fires, and report a fault condition when impaired.



Typical applications: aircraft hangars, fuel transfer stations, compressor stations, silane storage bunkers, paint spray booths and gas cabinets.

Specifications

Performance ratings

Responsive to hydrocarbon (gasoline, propane, methane, alcohol, JP-4, JP-3, etc). Also responsive to non-hydrocarbon (hydrogen, silane, hydrazine, etc) flames when special dual-pass IR sensor is used.

Third-party performance certified to detect:


- Saturating signal source in 50 milliseconds
- 1 square foot gasoline fire at 50 feet in 1 second
- 4 square foot aviation fuel fire at 100 feet in 5 seconds or less
- 100 square foot aviation fuel fire at 150 feet in 5 seconds or less
- Methane plume flame at 35 feet in 1 second

Additional performance with dual-pass infrared sensor:

- Silane plume flame 24 inches at 35 feet in 60 milliseconds
- Hydrogen plume flame 20 inches at 35 feet in 3 seconds
- Hydrazine 8 inch pool fire at 80 feet in 9.4 seconds

Environmental ratings

Rated:

Class I, Division 1, Groups B, C & D (explosion proof)
Class II, Division 1, Groups E, F & G (dust ignition proof)
NEMA 4X weatherproof, dust-tight, watertight
CE0081  II 2 G/D
Ex d IIB + H2 100°C (T5) for gas
Ex tD A21 IP66 T100°C for dust

Standard housing is copper-free aluminium conversion coated to MIL-C-5541C, Class 3 (white).
Optional stainless steel housing available with passive finish per MIL-5-5002C, Type 1.

Key features

- Patented Fire Event Analysis (FEA) algorithm for superior false-alarm immunity
- All inclusive three-year warranty on parts and labor
- Widest field of view in the industry (120°)
- Robust weatherproof enclosure for indoor or outdoor applications
- FM, CSA, and ATEX approved
- User selectable sensitivities
- Improved, advanced through-the-lens diagnostic self-test
- Long range detection
- Self-contained, explosion-proof enclosure
- Economical no-test version available
- Field configurable relays and sensitivity
- State-of-the-art microprocessor control with proprietary fire library
- High intensity, localized indication of fire or fault



Omniguard® model 860

Specifications (continued)

Standard operating temperature range:
-40° to +85°C (-40° to +185°F)

Spectral response

Ultraviolet

- Peak sensitivities of 220 µm

Infrared

- Standard: peak sensitivities of 4.4 µm
- Dual pass: peak sensitivities of 2.9 µm and 4.4 µm

Detector inputs

Inputs

- nominal voltage 24 VDC (ripple voltage <240mV)
- range 20 to 30 VDC

Power consumption

- standby 90 mA
- alarm 110 mA
- auto and manual test 250 mA

Detector outputs

Relay

- relays (2) fire, trouble, dry contacts, hermetically sealed
- rated 2 A at 28 VDC. User selects NO or NC
- fire relay user selects latching or non-latching

Current loop (standard version): 0 to 20 mA output

- 20 mA = fire
- 16 mA = UV or IR presence
- 4 mA = ready
- 0 mA = 20

Programmable RS-485 serial output.

Mechanical considerations

- Weight 5 lb (aluminium)
13 lb (stainless steel)
- Height x width 4.90 in x 5.50 in
- Conduit entry 3/4-14 NPTF or M20-1.5

Optional accessories

- Swivel mount No 4651027 (aircraft aluminium with SST locking devices)
No 70991 (all stainless steel)

Portable test unit Model 540

Air shield assembly kit No 8001023

Distributed by:



Edmonton: (780) 628-5759 Email: info@h2solutionsinc.com
Calgary: (403) 668-4534 Web: www.h2solutionsinc.com

Ordering information

To order, please specify

Type

Omniguard® model 860

Designation

Ultraviolet-infrared flame detector

Ordering number

860 - X X X O O

Fire type

- 0 Hydrocarbon
- 1 Hydrocarbon/non-hydrocarbon

Housing material/conduit entry

- 0 aluminium, 3/4-14 NPT (white)
- 2 stainless steel, 3/4-14 NPT
- 3 aluminium, M20-1.5 (white)
- 5 stainless steel, M20-1.5

Test feature

- 0 no self-test
- 1 auto self-test

Fire relay configuration

Agency approvals

Factory Mutual (FM)
ATEX
Canadian Standards Association (CSA)
California State Fire Marshall (CSFM)



Firefly AB

Phone: +46 (0)8 449 25 00

Fax: +46 (0)8 449 25 01

E-mail: omniguardsales@firefly.se

www.omniguardbyfirefly.se

Address

Textilgatan 31
120 30 Stockholm
Sweden

